

# Digital Crane Scale

Model : MSI3460

Digital crane scale with an ultra-bright LED digital display for long range viewing. The MSI3460 is a cost effective solution for light to medium capacity overhead weighing.

## FEATURES

- bright easy to read 38 mm high LED display with programmable brightness
- IP65 powder coated alodined cast aluminium corrosion resistant housing
- superior quality Crosby 360° non-bearing swivel
- 200% safe overload and 500% ultimate overload of rated capacity
- user programmable multifunction switch for use as TEST, UNIT select, NET/GROSS, TOTAL (auto or manual), PEAK HOLD and SETPOINTS
- maintains two counters. The first counts number of lifts for maintenance records and the second counts overloads for safety warnings
- 6 V rechargeable battery power
- precision +/- 0.1% accuracy of applied load
- units of measure lb or kg

## OPTIONS

- RF remote controller (control for On/Off, Zero, Tare and other functions) 15 m range
- audible setpoint alarm
- MS8000 RF wireless remote display & modem kit (must be factory fitted)



WIRELESS REMOTE  
DISPLAY

# Digital Crane Scale


Model : MSI3460

## STANDARD PRODUCT SPECIFICATIONS

Accuracy:	± (0.1% + 1d) of applied load
Display:	5 digit, 1.5 inch (38 mm) high LED; programmable brightness control
Filtering:	Off, Lo, Hi-1, Hi-2 selectable
Units:	Pounds or kilograms selectable
Resolution:	2000-3750 divisions standard (up to 10,000d available)
Power:	6 volt rechargeable battery (115/230 VAC rapid charge battery charger included)
Operating time:	Up to 50 hours depending on programmed operating mode
Auto-off mode:	Select for 15, 30, 45, 60 minutes or off
Auto sleep mode:	Power down during non-use and power up with weight change or any key press
Service counter:	Maintains two counters. The first counts number of lifts for inspection reminders and the second counts overloads for safety warnings.
Operating Temperature Range:	-4 °F + 122 °F (-20 °C to +50 °C)
Enclosure:	NEMA 4/IP65, powder coated alodined cast aluminium corrosion resistant
Hook:	Crosby 360 deg non-bearing swivel
Safe Overload:	200% of rated capacity
Ultimate Overload:	500% of rated capacity

## FUNCTION SWITCHES AND LIGHTS

Power:	Turns unit ON or OFF
Zero:	Zeros applied load up to 100% of capacity (limited range with NTEP and OIML configuration)
Tare:	Tares applied load and displays weight in net mode
User:	User programmable multifunction switch for use as TEST, UNIT select, NET/GROSS, TOTAL (auto or manual), PEAK HOLD and SETPOINTS
Annunciators:	COZ (Center of Zero), Net, Gross, Total, Peak, Low Battery, lb/kg, Motion, SP1, SP2, SP3, ACK IN, ACK OUT, RF
Calibration:	Digital



CAPACITY	RESOLUTION	A	B	C	D	E	F	APPROX SHIPPING WEIGHT
250lb 125kg	0.1lb .05kg	11.94in 303mm	2.0in 51mm	2.45in 62mm	1.63in 41mm	1.14in 29mm	1.16in 29mm	22lb 10kg
500lb 250kg	0.2lb 0.1kg	11.94in 303mm	2.0in 51mm	2.45in 62mm	1.63in 41mm	1.14in 29mm	1.16in 29mm	22lb 10kg
1000lb 500kg	0.5lb 0.2kg	11.94in 303mm	2.0in 51mm	2.45in 62mm	1.63in 41mm	1.14in 29mm	1.16in 29mm	22lb 10kg
2000lb 1000kg	1.0lb 0.5kg	11.94in 303mm	2.0in 51mm	2.45in 62mm	1.63in 41mm	1.14in 29mm	1.16in 29mm	22lb 10kg
5000lb 2500kg	2.0lb 1.0kg	16.67in 423mm	2.45in 62mm	3.40in 86mm	2.5in 64mm	1.81in 46mm	1.61in 41mm	39lb 18kg
10,000lb 5000kg	5.0lb 2.0kg	16.67in 423mm	2.45in 62mm	3.40in 86mm	2.5in 64mm	1.81in 46mm	1.61in 41mm	39lb 18kg
15,000lb 7,000kg	5.0lb 2.0kg	21.65in 550mm	3.25in 83mm	4.28in 109mm	3.00in 76mm	2.26in 57mm	2.08in 53mm	67lb 30kg

Specifications may change without notice

## WEIGHING SCALES

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT  
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS  
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

1300 970 111  
enquiries@wedderburn.com.au  
www.wedderburn.com.au