

Digital Crane Scale with Optional Remote Display

Model: WS600RF

The WS600RF crane scale is composed of a transmitting crane scale and various receiving weight indicators for overhead weighing and tension tasks (indicators detailed on page 2). This crane scale delivers safe, precise and efficient weighing solutions for any industrial environment that prohibits operator access or visibility to the scale hook.

FEATURES

- super bright 38 mm high red LED display
- cast aluminium alloyed housing
- patented load cell & overload protection design
- 360 degree swivel hook
- safe overload of 250 % of rated capacity
- ultimate overload of 500 % of rated capacity
- built-in rechargeable battery, up to 150 hours usage
- low battery power indication
- high accuracy up to 1/3000 achieved via triple weight ranges
- remote controller (as pictured)

OPTIONS

 variety of RF remote displays or display/printer all with 100 metre range



VARIATIONS

Model Number	Max Capacity	Graduation	Overall Dimensions (mm)
WS600RF1T5	1 500 kg	0.5 kg	235 (W) x 180 (D) x 600 (H)
WS600RF2T5	2 500 kg	1 kg	235 (W) x 180 (D) x 600 (H)

Specifications may change without notice

Digital Crane Scale with Optional Remote Display

Model: WS600RF

WS6RF15005A HANDHELD RF WEIGH INDICATOR

- black LCD 12 mm display with backlight
- power: "AA" size 1.5 V alkaline battery, 6 pcs (not included)
- up to 100 hours operating time, depending on backlight use
- key functions: ON/OFF, HOLD, TARE, NET/ GROSS, MODE, ZERO
- selectable automatic power-off for power setting



- wall mounted design
- RED 45 mm high LED display
- key functions: ON/OFF, HOLD, TARE, NET/GROSS, MODE, ZERO
- power: 220 V AC
- optional RS232C output, remote controller



WS6RF1023A LARGE DISPLAY RF WEIGHT INDICATOR

- wall mounted design
- RED 58 mm high LED display
- key functions: ON/OFF, HOLD, TARE, NET/GROSS, MODE, ZERO
- power: 220 V AC
- optional RS232C output, remote controller



WS6RF1040A SUPER LARGE DISPLAY RF WEIGHT INDICATOR WITH REMOTE CONTROLLER

- wall mounted design
- RED 100 mm high LED display
- remote keypad functions: ON/OFF, HOLD, TARE, NET/GROSS, MODE, ZERO
- power: 220 V AC
- optional RS232C output, remote controller




WS6RF1106A PRINTER TYPE RF WEIGHT INDICATOR

- large easy to read LCD display
- power: 220 V AC
- printer: impact dot matrix
- type size: 5 x 7 dot, 2.4 mm high, 24 characters per line
- printing speed: approx 1.7 lines / sec
- paper size (mm): 57 (width) x 60 (length) x 60 (diameter)
- weight data: DATE, PART NO., HIGH/LOW LIMIT WEIGHT, AUTO M+, TARE WEIGHT, NET WEIGHT, GROSS WEIGHT, TOTAL WEIGHT
- accessories: one ink ribbon, one paper roll
- optional RS232C output

DIMENSIONS

CAPACITY	1.5 T or 2.5 T	
А	235	
В	180	
С	600	
D	90	
E	80	
F	25 x 30	
G	30	
Net Weight (kg)	13.4	



Specifications may change without notice